



All support steelwork by others

©Tata Steel UK Limited.

#### Trisobuild™ 'U' Values

The depth below refers to both the minimum bracket & installation height to achieve the stated 'U' value when using a 1.25mm liner

Depth 280 = 0.15 W/m<sup>2</sup>K. (assuming an enhanced space)

Depth 240 = 0.18 W/m<sup>2</sup>K. (assuming an enhanced space)

Depth 210 = 0.20 W/m<sup>2</sup>K.

Depth 180 = 0.25 W/m<sup>2</sup>K.

Depth 140 = 0.30 W/m<sup>2</sup>K.

Depth 120 = 0.35 W/m<sup>2</sup>K.

#### Junction 'psi' and 'f' values

$\Psi = 0.002$  W/mK.

$f = 0.975$

Stated calculation results are dependent on components being as shown. Computer modelled in accordance with EN ISO 10211



LPCB 1815:1 Approved  
400674/15, 16 & 22

Tata Steel retains the right to amend the construction and technical specifications shown on this drawing without prior notice

**TATA STEEL**

SALES TEL: 01244 892199  
TECHNICAL TEL: 01244 892133 / 34

[www.tatasteelconstruction.com](http://www.tatasteelconstruction.com)

PROJECT **TYPICAL TRISOBUILD™  
HORIZONTAL WALL DETAILS**

TITLE **INTERNAL CORNER**

DRAWN BY **GMc**

SCALE **NTS**

APPROVED BY **DA**

TOLERANCES

DATE **18/11/09**

DRG. No.  
**W1-0010-03-B**