



**Trisobuild™ 'U' Values**

The depth below refers to both the minimum bracket & insulation height to achieve the stated 'U' value when using a LP1000 liner

- Depth 280 = 0.15 W/m²K. (assuming an enhanced spacer)
- Depth 240 = 0.18 W/m²K. (assuming an enhanced spacer)
- Depth 210 = 0.20 W/m²K.
- Depth 180 = 0.25 W/m²K.
- Depth 140 = 0.30 W/m²K.
- Depth 120 = 0.35 W/m²K.

Junction 'psi' and 'f' values

$\psi = \text{W/mK}.$

$f =$

Stated calculation results are dependent on components being as shown.  
Computer modelled in accordance with EN ISO 10211



*Tata Steel retain the right to amend the construction and technical specifications shown on this drawing without prior notice.*

**TATA STEEL**

SALES TEL: 01244 892199  
TECHNICAL TEL: 01244 892133 / 34  
[www.tatasteelconstruction.com](http://www.tatasteelconstruction.com)

PROJECT  
**TYPICAL TRISOBUILD™  
BUILT UP ROOF DETAIL**

TITLE  
**EXPANSION JOINT**

DRAWN BY GMC	SCALE NTS
-----------------	--------------

APPROVED BY DA	TOLERANCES
-------------------	------------

DATE <b>18/11/09</b>	DRG. No. R1-038-01-C
-------------------------	-------------------------